



Dimensions



LIDC



C023AV0049

AIR ECO 24° LED 2500lm/830 1x22W, FIX, RAL 9003


Description

MOUNTING	Suspended or ceiling surfaced lighting track system - suitable for ONETRACK (TRS)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Facet reflector (FRE)
BEAM ANGLE	24°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Housing: die-cast aluminium + sheet steel Reflector: facet anodized aluminium
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Coloured filters Various types of connections and suspension equipment (ONETRACK)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	2500 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	22 W
SYSTEM EFFICACY	109 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	174 x 89 x 120 mm
ROTATING	Up to 350°
PIVOTING	Up to 350°
WEIGHT	1 kg


AREAS OF APPLICATION ARCHITECTURE AND MEDIA

RETAIL AND PRESENTATION






Dimensions



LIDC



C023AV0050


AIR ECO 40° LED 2500lm/830 1x22W, FIX, RAL 9003

Description


MOUNTING	Suspended or ceiling surfaced lighting track system - suitable for ONETRACK (TRS)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Facet reflector (FRE)
BEAM ANGLE	40°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Housing: die-cast aluminium + sheet steel Reflector: facet anodized aluminium
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Coloured filters Various types of connections and suspension equipment (ONETRACK)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	2500 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	22 W
SYSTEM EFFICACY	109 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	174 x 89 x 120 mm
ROTATING	Up to 350°
PIVOTING	Up to 350°
WEIGHT	1 kg

AREAS OF APPLICATION ARCHITECTURE AND MEDIA
 RETAIL AND PRESENTATION






Dimensions



LIDC



K023AV0099

AIR ECO 24° LED 2300lm/840 1x21W, FIX, RAL 9003

Description

MOUNTING	Suspended or ceiling surfaced lighting track system - suitable for ONETRACK (TRS)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Facet reflector (FRE)
BEAM ANGLE	24°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Housing: die-cast aluminium + sheet steel Reflector: facet anodized aluminium
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Coloured filters Various types of connections and suspension equipment (ONETRACK)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	2300 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	21 W
SYSTEM EFFICACY	110 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	174 x 89 x 120 mm
ROTATING	Up to 350°
PIVOTING	Up to 350°
WEIGHT	1 kg

AREAS OF APPLICATION ARCHITECTURE AND MEDIA

RETAIL AND PRESENTATION

