

Dimensions



PV (ceiling 600 x 600)



K033AA0077

BATEN PV1 LED 3450lm/830 1x32W, FIX + EM 3H, RAL 9003

Description

MOUNTING	Ceiling recessed PVx / PRx - T-ceiling
LIGHT SOURCE	LED
OPTICAL SYSTEM	Opal diffuser (OPD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG) Emergency unit variant (3H)
MATERIALS	Diffuser: opal PMMA Heatsink: aluminium Housing: sheet steel Housing: white RAL 9003 (W03)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	3450 lm (370 lm-emergency unit)
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	32 W
SYSTEM EFFICACY	108 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	I
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B20
AMBIENT OPERATING TEMPERATURE	From +5 °C to +35 °C
IP PROTECTION DEGREE	IP20, optical part IP40
DIMENSIONS (L x W x H)	PV1: 595 x 595 x 70 mm
WEIGHT	6,5 kg

AREAS OF APPLICATION HEALTH AND CARE


RETAIL AND PRESENTATION

OFFICE





Dimensions



K033AA0078

BATEN PV1 LED 3450lm/830 1x32W, DALI + EM 3H, RAL 9003

Description

MOUNTING

Ceiling recessed
PVx / PRx - T-ceiling

LIGHT SOURCE

LED

OPTICAL SYSTEM

Opal diffuser (OPD)

LIGHT DISTRIBUTION

Direct

WIRING

Electronic control gear DALI (EDA)
Emergency unit variant (3H)

MATERIALS

Diffuser: opal PMMA
Heatsink: aluminium
Housing: sheet steel

SURFACE FINISH

Housing: white RAL 9003 (W03)

VOLTAGE

220-240 V, 50-60 Hz

POWER FACTOR

> 0,95

NET LUMEN OUTPUT (Ta=25°C)

3450 lm (370 lm-emergency unit)

LUMINOUS FLUX TOLERANCE

+/- 10 %

POWER CONSUMPTION

32 W

SYSTEM EFFICACY

108 lm/W

CORRELATED COLOUR TEMPERATURE

3000 K

COLOUR RENDERING INDEX

80 Ra

COLOUR TOLERANCE

3 SDCM

EEC

A++ / A+ / A

PROTECTION CLASS

I

THERMAL MANAGEMENT

Passive

SERVICE LIFETIME (Ta=25°C)

50,000 hours / L80 / B20

AMBIENT OPERATING TEMPERATURE

From +5 °C to +35 °C

IP PROTECTION DEGREE

IP20, optical part IP40

DIMENSIONS (L x W x H)

PV1: 595 x 595 x 70 mm

WEIGHT

6,5 kg

AREAS OF APPLICATION

HEALTH AND CARE

RETAIL AND PRESENTATION

OFFICE

