



Dimensions



LIDC



K023AR0292

ELYS TRACK 34° LED 1650lm/940 1x16W, FIX, RAL 9003

Description

MOUNTING	Suspended / ceiling surfaced - determined for continuous installation (MDS)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Facet reflector (FRE)
BEAM ANGLE	34°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Cover: transparent hardened glass Housing: die-cast aluminium Reflector: facet anodized aluminium
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Exchangeable reflectors Various types of connections and suspension equipment (ONETRACK)
VOLTAGE	220-240 V, 50-60 Hz
NET LUMEN OUTPUT (Ta=25°C)	1650 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	16 W
SYSTEM EFFICACY	103 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>90 Ra
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10 - 16W
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	172 x 92 x 155 mm
TILTING	Up to 350°
ROTATING	Up to 350°
WEIGHT	1 kg

AREAS OF APPLICATION ARCHITECTURE AND MEDIA

RETAIL AND PRESENTATION



5 YEARS WARRANTY



EEC A++/A+/A



HEAT SINK



MAINTENANCE FREE




UV/IR




ECO FRIENDLY




ENERGY SAVING



Dimensions



LIDC



K023AR0294

ELYS TRACK 34° LED 1650lm/940 1x16W, DALI, RAL 9003

Description

MOUNTING	Suspended / ceiling surfaced - determined for continuous installation (MDS)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Facet reflector (FRE)
BEAM ANGLE	34°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear DALI (EDA)
MATERIALS	Cover: transparent hardened glass Housing: die-cast aluminium Reflector: facet anodized aluminium
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Exchangeable reflectors Various types of connections and suspension equipment (ONETRACK)
VOLTAGE	220-240 V, 50-60 Hz
NET LUMEN OUTPUT (Ta=25°C)	1650 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	16 W
SYSTEM EFFICACY	103 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>90 Ra
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10 - 16W
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	172 x 92 x 155 mm
TILTING	Up to 350°
ROTATING	Up to 350°
WEIGHT	1 kg

AREAS OF APPLICATION  ARCHITECTURE AND MEDIA

 RETAIL AND PRESENTATION

