





Dimensions



LIDC



H004AG0003

TDO ECO LED M OPAL LED 3300lm/830 1x35W, FIX, -

Description

MOUNTING	Surfaced / Suspended (S/S)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Opal diffuser (OPD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Clips: PC Diffuser: PC Housing: grey injected polycarbonate Rope suspension
ACCESSORIES	220-240 V, 50-60 Hz
VOLTAGE	> 0,95
POWER FACTOR	3300 lm
NET LUMEN OUTPUT (Ta=25°C)	+/- 10 %
LUMINOUS FLUX TOLERANCE	35 W
POWER CONSUMPTION	94 lm/W
SYSTEM EFFICACY	3000 K
CORRELATED COLOUR TEMPERATURE	80 Ra
COLOUR RENDERING INDEX	A++ / A+ / A
EEC	I
PROTECTION CLASS	Passive
THERMAL MANAGEMENT	50,000 hours / L80 / B10
SERVICE LIFETIME (Ta=25°C)	From -20 °C to +35 °C
AMBIENT OPERATING TEMPERATURE	IP65
IP PROTECTION DEGREE	The luminaire is not suitable for use in outdoor applications
WARNING	IK08
MECHANICAL IMPACT RESISTANCE	1270 x 100 x 100 mm
DIMENSIONS (L x W x H)	2,3 kg
WEIGHT	

AREAS OF APPLICATION

- HOSPITALITY
- HOUSE AND FLAT
- INDUSTRY AND ENGINEERING
- HEALTH AND CARE

