





### Dimensions



### LIDC



# H004AG0175

TDO II ECO LED S OPAL LED 3250lm/840 1x24W, FIX, -

## Description

<b>MOUNTING</b>	Surfaced / Suspended (S/S)
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Opal diffuser (OPD)
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear FIX (ECG)
<b>MATERIALS</b>	Clips: PC / stainless steel (inox) Diffuser: PC Housing: grey injected polycarbonate
<b>ACCESSORIES</b>	Rope suspension
<b>VOLTAGE</b>	220-240 V, 50-60 Hz
<b>POWER FACTOR</b>	> 0,95
<b>NET LUMEN OUTPUT (Ta=25°C)</b>	3250 lm
<b>LUMINOUS FLUX TOLERANCE</b>	+/- 10 %
<b>POWER CONSUMPTION</b>	24 W
<b>SYSTEM EFFICACY</b>	135 lm/W
<b>CORRELATED COLOUR TEMPERATURE</b>	4000 K
<b>COLOUR RENDERING INDEX</b>	80 Ra
<b>COLOUR TOLERANCE</b>	3 SDCM
<b>EEC</b>	A++ / A+ / A
<b>PROTECTION CLASS</b>	I
<b>THERMAL MANAGEMENT</b>	Passive
<b>SERVICE LIFETIME (Ta=25°C)</b>	50,000 hours / L80 / B10
<b>AMBIENT OPERATING TEMPERATURE</b>	From -20 °C to +40 °C
<b>IP PROTECTION DEGREE</b>	IP65
<b>WARNING</b>	The luminaire is not suitable for use in outdoor applications
<b>MECHANICAL IMPACT RESISTANCE</b>	IK08
<b>DIMENSIONS (L x W x H)</b>	660 x 100 x 100 mm
<b>WEIGHT</b>	1,3 kg

### AREAS OF APPLICATION

- HOSPITALITY
- HOUSE AND FLAT
- INDUSTRY AND ENGINEERING
- HEALTH AND CARE

