





Dimensions



LIDC



H004AG0003

uTDO E M S/S 330083 135 ECG G35

TDO ECO LED M OPAL LED 3300lm/830 1x35W, FIX

Description

MOUNTING	Surfaced / Suspended (S/S)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Opal diffuser (OPD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Clips: PC Diffuser: PC Housing: grey injected polycarbonate
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	3300 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	35 W
SYSTEM EFFICACY	94 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	80 Ra
EEC	A++ / A+ / A
PROTECTION CLASS	I
THERMAL MANAGEMENT	Passive
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP65
WARNING	The luminaire is not suitable for use in outdoor applications
MECHANICAL IMPACT RESISTANCE	IK08
DIMENSIONS (L x W x H)	1270 x 100 x 100 mm
WEIGHT	1,8 kg

AREAS OF APPLICATION

- HOSPITALITY
- HOUSE AND FLAT
- INDUSTRY AND ENGINEERING
- HEALTH AND CARE

