




Dimensions



K002B00994

oPTS XS DWN MRE 75084 19 EDA W03

PRETTUS XS MATT REFLECTOR IP40 LED 750lm/840 1x9W, DALI

Description

MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Matt reflector (MRE)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear DALI (EDA)
MATERIALS	Diffuser: microprismatic PMMA Housing: sheet steel Reflector: matt anodised aluminium Trim: white RAL 9003 (W03)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	750 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	9 W
SYSTEM EFFICACY	83 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20, optical part IP40
DIMENSIONS	Diameter - 116 mm, height - 76 mm
OPENING	Diameter - 104 mm
WEIGHT	0,6 kg


AREAS OF APPLICATION EDUCATION

HOSPITALITY

HOUSE AND FLAT

HEALTH AND CARE

LIDC



 RETAIL AND PRESENTATION

 OFFICE



5 YEARS WARRANTY



EEC
A++A++P



HEAT
SINK



MAINTENANCE
FREE



UV/IR



ECO
FRIENDLY



ENERGY
SAVING

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.