


## Dimensions



# K002CH0648

oNVL L DWN APT 275083 133 EDA W03

**NOVIEL L ASYM POLISHED REFLECTOR+TRANSPARENT IP44  
LED 2750lm/830 1x33W, DALI**


## Description

<b>MOUNTING</b>	Ceiling recessed
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Asymmetric polished reflector + transparent cover (APT)
<b>LIGHT DISTRIBUTION</b>	Asymmetric
<b>WIRING</b>	Electronic control gear DALI (EDA)
<b>MATERIALS</b>	Cover: transparent PMMA Diffuser: microprismatic PMMA Housing: sheet steel Reflector: polished anodised aluminium Trim: sheet steel
<b>SURFACE FINISH</b>	Trim: white RAL 9003 (W03)
<b>VOLTAGE</b>	220-240 V, 50-60 Hz
<b>POWER FACTOR</b>	> 0,95
<b>NET LUMEN OUTPUT (Ta=25°C)</b>	2750 lm
<b>LUMINOUS FLUX TOLERANCE</b>	+/- 10 %
<b>POWER CONSUMPTION</b>	33 W
<b>SYSTEM EFFICACY</b>	83 lm/W
<b>CORRELATED COLOUR TEMPERATURE</b>	3000 K
<b>COLOUR RENDERING INDEX</b>	80 Ra
<b>COLOUR TOLERANCE</b>	3 SDCM
<b>EEC</b>	A++ / A+ / A
<b>PROTECTION CLASS</b>	II
<b>THERMAL MANAGEMENT</b>	Passive
<b>SERVICE LIFETIME (Ta=25°C)</b>	50,000 hours / L80 / B10
<b>AMBIENT OPERATING TEMPERATURE</b>	From -20 °C to +35 °C
<b>IP PROTECTION DEGREE</b>	IP20, optical part IP44
<b>DIMENSIONS (L x W x H)</b>	265 x 265 x 130 mm
<b>OPENING (L x W)</b>	250 x 250 mm
<b>WEIGHT</b>	1,5 kg

**AREAS OF APPLICATION**  ARCHITECTURE AND MEDIA

 RETAIL AND PRESENTATION

## LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.