



Dimensions



K019AK0266

oSML 1.5 MDS LWE 1030084 177 ECG W03

SMART-L LWE LED 10300lm/840 1x77W, FIX

Description

| | |
|--------------------------------------|---|
| MOUNTING | Suspended / ceiling surfaced - determined for continuous installation (MDS) |
| LIGHT SOURCE | LED |
| OPTICAL SYSTEM | Wide lenses (LWE) |
| BEAM ANGLE | 93°, 91° |
| LIGHT DISTRIBUTION | Direct |
| WIRING | Electronic control gear FIX (ECG) |
| MATERIALS | Housing: sheet steel Lenses: PMMA |
| SURFACE FINISH | Housing: white RAL 9003 (W03) |
| ACCESSORIES | Components for system PRESTIGE Anti-glare grid |
| VOLTAGE | 220-240 V, 50-60 Hz |
| NET LUMEN OUTPUT (Ta=25°C) | 10300 lm |
| LUMINOUS FLUX TOLERANCE | +/- 10 % |
| POWER CONSUMPTION | 77 W |
| SYSTEM EFFICACY | 134 lm/W |
| CORRELATED COLOUR TEMPERATURE | 4000 K |
| COLOUR RENDERING INDEX | >80 Ra |
| SERVICE LIFETIME (Ta=25°C) | 50,000 hours / L80 / B10 |
| AMBIENT OPERATING TEMPERATURE | From -20 °C to +35 °C |
| IP PROTECTION DEGREE | IP20 |
| DIMENSIONS (L x W x H) | 1482 x 72 x 88 mm |
| WEIGHT | 2,8 kg |

AREAS OF APPLICATION ARCHITECTURE AND MEDIA

EDUCATION


SPORT AND LEISURE

INDUSTRY AND ENGINEERING

RETAIL AND PRESENTATION



LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.