

## Dimensions



## Accessories



# K056AC0006

uSNA PV1 MCD 420084 143 ECG W16

**SANA PV-1 MICROPRISMA LED 4200lm/840 1x43W, FIX**

## Description


<b>MOUNTING</b>	Ceiling recessed PV1 - T-ceiling
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Microprismatic diffuser (MCD)
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear FIX (ECG)
<b>MATERIALS</b>	Diffuser: PC Housing: aluminium
<b>SURFACE FINISH</b>	Housing: white RAL 9016 (W16)
<b>ACCESSORIES</b>	Rope suspension Frame for plasterboard installation Frame for surfaced installation
<b>VOLTAGE</b>	220-240 V, 50-60 Hz
<b>POWER FACTOR</b>	> 0,95
<b>NET LUMEN OUTPUT (Ta=25°C)</b>	4200 lm
<b>LUMINOUS FLUX TOLERANCE</b>	+/- 10 %
<b>POWER CONSUMPTION</b>	43 W
<b>SYSTEM EFFICACY</b>	98 lm/W
<b>CORRELATED COLOUR TEMPERATURE</b>	4000 K
<b>COLOUR RENDERING INDEX</b>	80 Ra
<b>COLOUR TOLERANCE</b>	6 SDCM
<b>EEC</b>	A++ / A+ / A
<b>PROTECTION CLASS</b>	II
<b>THERMAL MANAGEMENT</b>	Passive
<b>SERVICE LIFETIME (Ta=25°C)</b>	50,000 hours / L70 / B50
<b>AMBIENT OPERATING TEMPERATURE</b>	From -20 °C to +35 °C
<b>IP PROTECTION DEGREE</b>	IP20, optical part IP40
<b>DIMENSIONS (L x W x H)</b>	PV1: 595 x 595 x 10 mm
<b>WEIGHT</b>	4,1 kg

**AREAS OF APPLICATION** EDUCATION

HOSPITALITY

HEALTH AND CARE

## LIDC



OFFICE



5 YEARS WARRANTY



EEC  
A++/A+/A



HEAT  
SINK



MAINTENANCE  
FREE



UV/IR



ECO  
FRIENDLY



ENERGY  
SAVING

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.