

Dimensions



Accessories



K056AC0014

uSNA PR1 MCD 420084 143 ECG W16

SANA PR-1 MICROPRISMA LED 4200lm/840 1x43W, FIX

Description


MOUNTING	Ceiling recessed PR1 - T-ceiling
LIGHT SOURCE	LED
OPTICAL SYSTEM	Microprismatic diffuser (MCD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Diffuser: PC Housing: aluminium
SURFACE FINISH	Housing: white RAL 9016 (W16)
ACCESSORIES	Rope suspension Frame for plasterboard installation Frame for surfaced installation
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	4200 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	43 W
SYSTEM EFFICACY	98 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	6 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L70 / B50
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20, optical part IP40
DIMENSIONS (L x W x H)	PR1: 620 x 620 x 10 mm
WEIGHT	4,1 kg

AREAS OF APPLICATION EDUCATION

HOSPITALITY

HEALTH AND CARE

LIDC



OFFICE



5 YEARS WARRANTY



EEC
A++/A+/A



HEAT
SINK



MAINTENANCE
FREE



UV/IR



ECO
FRIENDLY



ENERGY
SAVING

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.