



LED

up to
5500
lm

Mounting	Ground Recessed
LED Device	high power LEDs
LED color variants	3000K / 4000K / 5700K
Input Voltage	48 V DC
Power cable connection	Outdoor cable H05RR-F 2x1,5mm (L=0,5m)
Service lifetime	70,000 hrs / L70 @25°C
Operating ambient tem.	-20°C / +40°C
Materials	housing: die cast aluminium cover: clear hardened glass, stainless steel frame
Dimensions	18 WHITE: 72 x 80 x (L) 650 mm 24 WHITE: 72 x 80 x (L) 950 mm 36 WHITE: 72 x 80 x (L) 1250 mm
Accessories (not included):	constant Voltage 48V power supply

AEDI LINE PARVUS GROUND 18/24/36 WHITE

The stylishly modern and unassuming exterior of AEDI LINE PARVUS houses state-of-the-art WHITE LED technology and made using the highest quality materials and construction methods. Bringing the flexibility to outdoor application, this powerful lighting fixture is ideally suited to use in landscape and building illumination, and IP67 ensures safe operation in even the most demanding areas.

Type	net lumen output (at Ta = 25 °C)	power consumption	LED Device	beam angle	weight
	(lm)	W (mA)	(LEDs Pcs.)		(kg)
AEDI LINE PARVUS 18 WHITE	2268	18 (350) / 33 (600)	18	Spot / Narrow / Medium / Wide / Asym.	2.75
AEDI LINE PARVUS 24 WHITE	3402	27 (350) / 48 (600)	24	Spot / Narrow / Medium / Wide / Asym.	3.75
AEDI LINE PARVUS 36 WHITE	4536	36 (350) / 64,5 (600)	36	Spot / Narrow / Medium / Wide / Asym.	4.75

