



PRODUCT DETAILS



Dimensions



Accessories



GHADA 1 SUSPENDED

GHADA 1 SUSPENDED LMW LED
14300lm/840 1x123, FIX, RAL 9005

DOWNLOADS

[Certificates](#)
[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description


MOUNTING	Suspended (SSD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Medium wide lenses (LMW)
BEAM ANGLE	66°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Cover: transparent hardened glass Housing: die-cast aluminium + sheet steel Chain suspension Lenses: PMMA
SURFACE FINISH	Housing: black RAL 9005 (B05)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,98
NET LUMEN OUTPUT (Ta=25°C)	14300 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	123 W
SYSTEM EFFICACY	116 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>80 Ra
COLOUR TOLERANCE	5 SDCM
PROTECTION CLASS	I
SERVICE LIFETIME (Ta=25°C)	100,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -40 °C to +45 °C
IP PROTECTION DEGREE	IP65
WARNING	The luminaire is not suitable for use in outdoor applications
MECHANICAL IMPACT RESISTANCE	IK07
DIMENSIONS (L x W x H)	636 x 166 x 83 mm
WEIGHT	7,2 kg

AREAS OF APPLICATION SPORT AND LEISURE

INDUSTRY AND ENGINEERING

06661150 → 903032
000
000

LIDC



RETAIL AND PRESENTATION



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.