




PRODUCT DETAILS



Dimensions



Accessories



MYAR II SUSPENDED

MYAR II SUSPENDED PRD LED
34100lm/850 1x273W, DALI, RAL 9005


DOWNLOADS

[Certificates](#)
[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)


Description

MOUNTING	Suspended (SSD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Prismatic diffuser (PRD)
BEAM ANGLE	98°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear DALI (EDA)
MATERIALS	Diffuser: PMMA + glass Housing: die-cast aluminium + sheet steel
SURFACE FINISH	Housing: black RAL 9005 (B05)
ACCESSORIES	Protective foil available for food industry applications according to IFS (International Food Standard) Chain suspension CHS 65 Reflector 60°/80°/100°
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	0,98
NET LUMEN OUTPUT (Ta=25°C)	34100 lm
NUMBER OF LAMPS	1
POWER CONSUMPTION	273 W
SYSTEM EFFICACY	125 lm/W
CORRELATED COLOUR TEMPERATURE	5000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
PROTECTION CLASS	I
SERVICE LIFETIME (Ta=25°C)	100,000 hours/L80/B10 (at 25°C) - 273 W
AMBIENT OPERATING TEMPERATURE	From -40°C to +45°C (273W EDA)
IP PROTECTION DEGREE	IP66
MECHANICAL IMPACT RESISTANCE	IK09
DIMENSIONS (L x W x H)	380 x 380 x 148 mm
WEIGHT	15,3 kg

AREAS OF APPLICATION  ARCHITECTURE AND MEDIA



LIDC



SPORT AND LEISURE

INDUSTRY AND ENGINEERING

RETAIL AND PRESENTATION



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.