




## PRODUCT DETAILS



## Dimensions



## Accessories



# MYAR II SURFACED

**MYAR II SURFACED PRD LED 33300lm/840  
1x273W, FIX, RAL 9005**

## DOWNLOADS

[Certificates](#)  
[Datasheet](#)  
[Product sheet](#)  
[Installation manual](#)  
[IES file](#)  
[LDT file](#)  
[EEC](#)

## Description

<b>MOUNTING</b>	Ceiling surfaced (SFD)
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Prismatic diffuser (PRD)
<b>BEAM ANGLE</b>	98°
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear FIX (ECG)
<b>MATERIALS</b>	Diffuser: PMMA + glass Housing: die-cast aluminium + sheet steel
<b>SURFACE FINISH</b>	Housing: black RAL 9005 (B05)
<b>ACCESSORIES</b>	Protective foil available for food industry applications according to IFS (International Food Standard) Reflector 60°/80°/100°
<b>VOLTAGE</b>	220-240 V, 50-60 Hz
<b>POWER FACTOR</b>	0,98
<b>NET LUMEN OUTPUT (Ta=25°C)</b>	33300 lm
<b>NUMBER OF LAMPS</b>	1
<b>POWER CONSUMPTION</b>	273 W
<b>SYSTEM EFFICACY</b>	122 lm/W
<b>CORRELATED COLOUR TEMPERATURE</b>	4000 K
<b>COLOUR RENDERING INDEX</b>	80 Ra
<b>COLOUR TOLERANCE</b>	3 SDCM
<b>PROTECTION CLASS</b>	I
<b>SERVICE LIFETIME (Ta=25°C)</b>	100,000 hours/L80/B10 (at 25°C) - 273 W
<b>AMBIENT OPERATING TEMPERATURE</b>	From -40°C to +50°C (273W ECG)
<b>IP PROTECTION DEGREE</b>	IP66
<b>MECHANICAL IMPACT RESISTANCE</b>	IK09
<b>DIMENSIONS (L x W x H)</b>	380 x 380 x 218 mm
<b>WEIGHT</b>	17,5 kg

**AREAS OF APPLICATION**  ARCHITECTURE AND MEDIA

 SPORT AND LEISURE




INDUSTRY AND ENGINEERING

RETAIL AND PRESENTATION



## LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.