



## PRODUCT DETAILS



## Dimensions



## Accessories



# MYAR II SURFACED

MYAR II SURFACED PRD LED 34800lm/850  
1x270W, DALI, RAL 9005

## DOWNLOADS

[Certificates](#)  
[Datasheet](#)  
[Product sheet](#)  
[Installation manual](#)  
[IES file](#)  
[LDT file](#)  
[EEC](#)

## Description

<b>MOUNTING</b>	Ceiling surfaced (SFD)
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Prismatic diffuser (PRD)
<b>BEAM ANGLE</b>	98°
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear DALI (EDA)
<b>MATERIALS</b>	Diffuser: PMMA + glass Housing: die-cast aluminium + sheet steel
<b>SURFACE FINISH</b>	Housing: black RAL 9005 (B05)
<b>ACCESSORIES</b>	Protective foil available for food industry applications according to IFS (International Food Standard) Reflector 60°/80°/100°
<b>VOLTAGE</b>	220-240 V, 50-60 Hz
<b>POWER FACTOR</b>	0,98
<b>NET LUMEN OUTPUT (Ta=25°C)</b>	34800 lm
<b>NUMBER OF LAMPS</b>	1
<b>POWER CONSUMPTION</b>	270 W
<b>SYSTEM EFFICACY</b>	129 lm/W
<b>CORRELATED COLOUR TEMPERATURE</b>	5000 K
<b>COLOUR RENDERING INDEX</b>	>80 Ra
<b>COLOUR TOLERANCE</b>	3 SDCM
<b>PROTECTION CLASS</b>	I
<b>SERVICE LIFETIME (Ta=25°C)</b>	100,000 hours / L80 / B10 - 273W
<b>AMBIENT OPERATING TEMPERATURE</b>	From -40°C to +45°C (273W EDA)
<b>IP PROTECTION DEGREE</b>	IP66
<b>MECHANICAL IMPACT RESISTANCE</b>	IK09
<b>DIMENSIONS (L x W x H)</b>	380 x 380 x 218 mm
<b>WEIGHT</b>	17,5 kg

**AREAS OF APPLICATION** ARCHITECTURE AND MEDIA

SPORT AND LEISURE



INDUSTRY AND ENGINEERING

RETAIL AND PRESENTATION

LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.