



PRODUCT DETAILS



Dimensions



Accessories



PRETTUS II S

PRETTUS II S POLISHED REF LED
2150lm/830 1x19W, FIX, RAL 9003

DOWNLOADS


[Certificates](#)
[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Polished reflector (PRE)
BEAM ANGLE	65°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Diffuser: microprismatic PMMA Housing: sheet steel Reflector: anodised aluminium Trim: die cast aluminium Trim: white RAL 9003 (W03)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	0,90
NET LUMEN OUTPUT (Ta=25°C)	2150 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	19 W
SYSTEM EFFICACY	113 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	>80 Ra >90 Ra - on request
COLOUR TOLERANCE	3 SDCM
PROTECTION CLASS	II
SERVICE LIFETIME (Ta=25°C)	100,000 hours / L90 / B20
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20, optical part IP40
DIMENSIONS	Diameter - 166 mm, height - 113 mm
OPENING	Diameter - 154 mm
WEIGHT	0,8 kg

AREAS OF APPLICATION EDUCATION
 HOSPITALITY
 HOUSE AND FLAT

LIDC



HEALTH AND CARE

RETAIL AND PRESENTATION

OFFICE



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.