



PRODUCT DETAILS



Dimensions



Accessories



AIR IB

**AIR IB 40° LED 2250lm/830 1x21W, FIX,
RAL 9003**

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Suspended or ceiling surfaced lighting track system - suitable for ONETRACK (TRS)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Facet reflector (FRE)
BEAM ANGLE	40°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Housing: die-cast aluminium + sheet steel Reflector: facet anodised aluminium
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Various types of connections and suspension equipment (ONETRACK)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	0,95
NET LUMEN OUTPUT (Ta=25°C)	2250 lm
POWER CONSUMPTION	21 W
SYSTEM EFFICACY	107 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	>80 Ra
COLOUR TOLERANCE	3 SDCM
PROTECTION CLASS	II
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	162 x 110 x 154 mm
TILTING	+/- 175°
ROTATING	+/- 175°
WEIGHT	0,7 kg


AREAS OF APPLICATION ARCHITECTURE AND MEDIA

RETAIL AND PRESENTATION





LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.