



PRODUCT DETAILS



Dimensions



Accessories



SKAT

**SKAT LA2 LED 10900lm/840 1x79W, FIX,
RAL 9003**

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description


| | |
|--------------------------------------|---|
| MOUNTING | Suspended or ceiling surfaced lighting track system - suitable for ONETRACK (TRS) |
| LIGHT SOURCE | LED |
| OPTICAL SYSTEM | Double asymmetric lenses (LA2) |
| BEAM ANGLE | 74°, 134° |
| LIGHT DISTRIBUTION | Direct |
| WIRING | Electronic control gear FIX (ECG) |
| MATERIALS | Housing: sheet steel Lenses: PMMA |
| SURFACE FINISH | Housing: white RAL 9003 (W03) |
| ACCESSORIES | Various types of connections and suspension equipment (ONETRACK) |
| VOLTAGE | 220-240 V, 50-60 Hz |
| POWER FACTOR | 0,97 |
| NET LUMEN OUTPUT (Ta=25°C) | 10900 lm |
| POWER CONSUMPTION | 79 W |
| SYSTEM EFFICACY | 138 lm/W |
| CORRELATED COLOUR TEMPERATURE | 4000 K |
| COLOUR RENDERING INDEX | >80 Ra |
| COLOUR TOLERANCE | 3 SDCM |
| PROTECTION CLASS | I |
| SERVICE LIFETIME (Ta=25°C) | 100,000 hours / L90 / B20 |
| AMBIENT OPERATING TEMPERATURE | From -20 °C to +30 °C |
| IP PROTECTION DEGREE | IP20 |
| DIMENSIONS (L x W x H) | 578 x 190 x 61 mm |
| WEIGHT | 2,9 kg |

AREAS OF APPLICATION ARCHITECTURE AND MEDIA
 RETAIL AND PRESENTATION





LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.