



PRODUCT DETAILS



Dimensions



Accessories



LAMBDA LED D-I S+

**LAMBDA LED D-I S+ L LED 6200lm/840
1x42W, DALI + SENSOR (D2S), RAL 9003**

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description


MOUNTING	Suspended (SSD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Microprismatic diffuser (MCD)
BEAM ANGLE	75°, 85°
LIGHT DISTRIBUTION	Direct-indirect
WIRING	External lead-in flexible cable Electronic control gear DALI + SENSOR (D2S)
MATERIALS	Diffuser: PMMA Housing: sheet steel
SURFACE FINISH	Housing: white RAL 9003 (W03)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	6200 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	42 W
SYSTEM EFFICACY	148 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>80 Ra
COLOUR TOLERANCE	3 SDCM
PROTECTION CLASS	I
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	1560 x 120 x 60 mm
WEIGHT	6,2 kg

AREAS OF APPLICATION EDUCATION


HEALTH AND CARE

OFFICE





LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.