




PRODUCT DETAILS



Dimensions



Accessories



LAMBDA LINE LED D-I

**LAMBDA LINE LED D-I M T LED 5500lm/840
1x37W, DALI, RAL 9003**

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)


Description

MOUNTING	Suspended - determined for continuous installation (MDS)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Microprismatic diffuser (MCD)
BEAM ANGLE	75°, 85°
LIGHT DISTRIBUTION	Direct-indirect
WIRING	Electronic control gear DALI (EDA) Through wiring (F, T version)
MATERIALS	Diffuser: PMMA Housing: sheet steel
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Rope suspension RS-S 58
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	0,96
NET LUMEN OUTPUT (Ta=25°C)	5500 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	37 W
SYSTEM EFFICACY	149 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>80 Ra
COLOUR TOLERANCE	3 SDCM
PROTECTION CLASS	I
AMBIENT OPERATING TEMPERATURE	From -25 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	1260 x 120 x 60 mm
WEIGHT	4,9 kg


AREAS OF APPLICATION EDUCATION

HEALTH AND CARE

OFFICE



LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.