




## PRODUCT DETAILS



## Dimensions



## Accessories



# INDIRECT LED

**INDIRECT LED PR1 LED 3700lm/840**  
**1x35W, FIX + EM 3H, RAL 9003**

## DOWNLOADS

[Datasheet](#)  
[Product sheet](#)  
[Installation manual](#)  
[IES file](#)  
[LDT file](#)  
[EEC](#)

## Description

<b>MOUNTING</b>	Ceiling recessed PRx - T-ceiling
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Matt parabolic louvre PAR MAT-V2 (ML2)
<b>BEAM ANGLE</b>	75°, 95°
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear FIX (ECG) Emergency unit variant (3H, ECG)
<b>MATERIALS</b>	Diffuser: PMMA Housing: sheet steel Parabolic louvre: matt anodised aluminium Shade: sheet steel perforated Housing: white RAL 9003 (W03)
<b>SURFACE FINISH</b>	Frame for plasterboard installation
<b>ACCESSORIES</b>	220-240 V, 50-60 Hz
<b>VOLTAGE</b>	0,97
<b>POWER FACTOR</b>	3700 lm (360 lm - emergency unit)
<b>NET LUMEN OUTPUT (Ta=25°C)</b>	+/- 10 %
<b>LUMINOUS FLUX TOLERANCE</b>	35 W
<b>POWER CONSUMPTION</b>	106 lm/W
<b>SYSTEM EFFICACY</b>	4000 K
<b>CORRELATED COLOUR TEMPERATURE</b>	>80 Ra
<b>COLOUR RENDERING INDEX</b>	3 SDCM
<b>COLOUR TOLERANCE</b>	I
<b>PROTECTION CLASS</b>	100,000 hours / L90 / B20
<b>SERVICE LIFETIME (Ta=25°C)</b>	From -25 °C to +35 °C (from +5°C with EM unit)
<b>AMBIENT OPERATING TEMPERATURE</b>	IP20
<b>IP PROTECTION DEGREE</b>	PR1: 620 x 620 x 91 mm
<b>DIMENSIONS (L x W x H)</b>	4,7 kg
<b>WEIGHT</b>	


## AREAS OF APPLICATION

- EDUCATION
- HOSPITALITY
- OFFICE



---

## LIDC



---

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.