




## PRODUCT DETAILS



## Dimensions



## Accessories



# SIMPLE LS CORRIDOR

## SIMPLE LS CORRIDOR LCO LED

8450lm/840 1x61W, DALI, RAL 9003

## DOWNLOADS

[Datasheet](#)  
[Product sheet](#)  
[Installation manual](#)  
[IES file](#)  
[LDT file](#)  
[EEC](#)

## Description

<b>MOUNTING</b>	Suspended or ceiling surfaced - determined for continuous installation (MDS)
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Corridor lenses (LCO)
<b>BEAM ANGLE</b>	45°, 90°
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear DALI (EDA)
<b>MATERIALS</b>	End caps: PS Housing: sheet steel Lenses: PMMA
<b>SURFACE FINISH</b>	Housing: white RAL 9003 (W03)
<b>ACCESSORIES</b>	Connection piece Piece without wiring DUMMY Additional through wiring Rope suspension RS-S 09, RS-C 21/09
<b>VOLTAGE</b>	220-240 V, 50-60 Hz
<b>POWER FACTOR</b>	0,97
<b>NET LUMEN OUTPUT (Ta=25°C)</b>	8450 lm
<b>LUMINOUS FLUX TOLERANCE</b>	+/- 10 %
<b>POWER CONSUMPTION</b>	61 W
<b>SYSTEM EFFICACY</b>	139 lm/W
<b>CORRELATED COLOUR TEMPERATURE</b>	4000 K
<b>COLOUR RENDERING INDEX</b>	>80 Ra
<b>COLOUR TOLERANCE</b>	3 SDCM
<b>PROTECTION CLASS</b>	I
<b>SERVICE LIFETIME (Ta=25°C)</b>	100,000 hours / L90 / B50
<b>AMBIENT OPERATING TEMPERATURE</b>	From -20 °C to +35 °C
<b>IP PROTECTION DEGREE</b>	IP20
<b>DIMENSIONS (L x W x H)</b>	1484 x 63 x 70 mm
<b>WEIGHT</b>	3 kg

**AREAS OF APPLICATION** ARCHITECTURE AND MEDIA



--- 903004

KS-09 L150 RD W



--- 305171

Additional through wiring Ø EC3 3 x 1.5 mm²



--- 903 016

KS-09 L150 SQ W



--- 305172

Additional through wiring Ø IDA 3 x 1.5 mm²



Correction piece --- 305170

KS-C 2x09 L150




--- 903042



--- 305169

Piece without wiring Ø ØUB67

## LIDC



EDUCATION

INDUSTRY AND ENGINEERING

RETAIL AND PRESENTATION



5 YEARS WARRANTY



EEC A++/A+/A



MAINTENANCE FREE



UV/IR



ECO FRIENDLY



ENERGY SAVING

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.