



PRODUCT DETAILS



Dimensions



Accessories



MILINE UNO SURFACED

MILINE UNO SURFACED L LWL LED

5500lm/830 1x38W, FIX + EM 3H, RAL 9003

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description


MOUNTING	Ceiling surfaced (SFD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Lenses + white louvre (LWL)
BEAM ANGLE	80°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG) Emergency unit variant (3H, ECG)
MATERIALS	Housing: sheet steel Louvre: polycarbonate Housing: white RAL 9003 (W03)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	0,97
NET LUMEN OUTPUT (Ta=25°C)	5500 lm (490 lm - emergency unit)
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	38 W
SYSTEM EFFICACY	145 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	>80 Ra
COLOUR TOLERANCE	3 SDCM
PROTECTION CLASS	I
SERVICE LIFETIME (Ta=25°C)	100,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -25 °C to +35 °C (from +5°C with EM unit)
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	1421 x 61 x 74 mm
WEIGHT	3,3 kg

AREAS OF APPLICATION EDUCATION

HEALTH AND CARE

OFFICE

LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.