



PRODUCT DETAILS



Dimensions



Accessories



MILINE UNO SURFACED

MILINE UNO SURFACED M LBL LED
4100lm/830 1x31W, DALI, RAL 9003

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

| | |
|--------------------------------------|---|
| MOUNTING | Ceiling surfaced (SFD) |
| LIGHT SOURCE | LED |
| OPTICAL SYSTEM | Lenses + black louvre (LBL) |
| BEAM ANGLE | 80° |
| LIGHT DISTRIBUTION | Direct |
| WIRING | Electronic control gear DALI (EDA) |
| MATERIALS | Housing: sheet steel Louvre: polycarbonate |
| SURFACE FINISH | Housing: white RAL 9003 (W03) |
| VOLTAGE | 220-240 V, 50-60 Hz |
| POWER FACTOR | 0,97 |
| NET LUMEN OUTPUT (Ta=25°C) | 4100 lm |
| LUMINOUS FLUX TOLERANCE | +/- 10 % |
| POWER CONSUMPTION | 31 W |
| SYSTEM EFFICACY | 132 lm/W |
| CORRELATED COLOUR TEMPERATURE | 3000 K |
| COLOUR RENDERING INDEX | >80 Ra |
| COLOUR TOLERANCE | 3 SDCM |
| PROTECTION CLASS | I |
| SERVICE LIFETIME (Ta=25°C) | 100,000 hours / L80 / B10 |
| AMBIENT OPERATING TEMPERATURE | From -25 °C to +35 °C |
| IP PROTECTION DEGREE | IP20 |
| DIMENSIONS (L x W x H) | 1141 x 61 x 74 mm |
| WEIGHT | 2,8 kg |


AREAS OF APPLICATION EDUCATION

HEALTH AND CARE

OFFICE



LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.