


PRODUCT DETAILS



Dimensions



Accessories



MILINE DUO LINE RECESSED

**MILINE DUO LINE RECESSED L L LED 7950lm/830 1x52W,
DALI, RAL 9003**

DOWNLOADS


[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Ceiling recessed - determined for continuous installation (RCD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Lenses + white louvre (LWL)
BEAM ANGLE	80°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear DALI (EDA)
MATERIALS	Housing: sheet steel Louvre: polycarbonate
SURFACE FINISH	Housing: white RAL 9003 (W03)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	0,97
NET LUMEN OUTPUT (Ta=25°C)	7950 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	52 W
SYSTEM EFFICACY	153 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	>80 Ra
COLOUR TOLERANCE	3 SDCM
PROTECTION CLASS	I
SERVICE LIFETIME (Ta=25°C)	100,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -25 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	1412 x 105 x 61 mm
OPENING (L x W)	1406 x 95 mm
WEIGHT	2,5 kg

AREAS OF APPLICATION EDUCATION

LIDC



 OFFICE



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.