



PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



DOWNLOADS

[Datasheet](#)

[Installation manual](#)

TARF RECESSED

Description

MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Facet matt reflector (FRM)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX / DALI (ECG / EDA)
MATERIALS	Housing: sheet steel Reflector: facet anodized aluminium Trim: sheet steel
SURFACE FINISH	Trim: white RAL 9003 (W03)
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +40 °C

AREAS OF APPLICATION

- HOSPITALITY
- HOUSE AND FLAT
- HEALTH AND CARE
- RETAIL AND PRESENTATION



Accessories

List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
TARF RECESSED FACET REF LED 1000lm/830 1x12W, FIX, RAL 9003	Updated	RFA / 3DS / IES / LDT / CURVE /
TARF RECESSED FACET REF LED 1050lm/840 1x12W, FIX, RAL 9003	Updated	RFA / 3DS / IES / LDT / CURVE /
TARF RECESSED FACET REF LED 1000lm/830 1x12W, DALI, RAL 9003	Updated	RFA / 3DS / IES / LDT / CURVE /
TARF RECESSED FACET REF LED 1050lm/840 1x12W, DALI, RAL 9003	Updated	RFA / 3DS / IES / LDT / CURVE /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.