




PRODUCT DETAILS



Dimensions



Accessories



GRAFIAS SUSPENDED

**GRAFIAS SUSPENDED POLISHED REF +
TRANSPARENT COVER LED 12700lm/850 1x88W, DALI, RAL
9005**

DOWNLOADS


[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Suspended (SSD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Polished reflector + transparent cover (PRT)
BEAM ANGLE	70°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear DALI (EDA)
MATERIALS	Cover: transparent hardened glass Housing: die-cast aluminium Reflector: evaporative coated PC
SURFACE FINISH	Housing: black RAL 9005 (B05)
ACCESSORIES	Chain suspension system: X2 - for 2 luminaires X4 - for 4 luminaires X1 - for 1 luminaire (Ballproof version)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	12700 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	88 W
SYSTEM EFFICACY	144 lm/W
CORRELATED COLOUR TEMPERATURE	5000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	5 SDCM
PROTECTION CLASS	I
SERVICE LIFETIME (Ta=25°C)	100,000 hours / L90 / B10
AMBIENT OPERATING TEMPERATURE	From -40 °C to +45 °C
IP PROTECTION DEGREE	IP66
WARNING	The luminaire is not suitable for use in outdoor applications
MECHANICAL IMPACT RESISTANCE	IK07
DIMENSIONS (L x W x H)	345 x 345 x 83 mm



LIDC



WEIGHT

9,5 kg

AREAS OF APPLICATION

 SPORT AND LEISURE

 INDUSTRY AND ENGINEERING

 RETAIL AND PRESENTATION



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.