



PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



Accessories



DOWNLOADS

[Datasheet](#)

[Installation manual](#)

ZIPAR ADJUSTABLE

Description Product map

MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Facet reflector (FRE)
BEAM ANGLE	24° 40°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX / DALI (ECG / EDA)
MATERIALS	Housing: sheet steel + extruded aluminium Reflector: facet anodised aluminium
SURFACE FINISH	Housing: white RAL 9003 (W03)
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C

AREAS OF APPLICATION ARCHITECTURE AND MEDIA

RETAIL AND PRESENTATION



List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
ZIPAR ADJUSTABLE 24° LED 1500lm/830 1x12W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 24° LED 1550lm/840 1x12W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 24° LED 2400lm/830 1x19W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 24° LED 2500lm/840 1x19W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 24° LED 3550lm/830 1x31W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 24° LED 3650lm/840 1x31W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 40° LED 1500lm/830 1x12W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 40° LED 1550lm/840 1x12W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 40° LED 2400lm/830 1x19W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 40° LED 2500lm/840 1x19W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 40° LED 3550lm/830 1x31W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 40° LED 3650lm/840 1x31W, FIX, RAL 9003		RFA / 3DS / IES / LDT /

ZIPAR ADJUSTABLE 24° LED 1500lm/830 1x12W, DALI, RAL 9003	CURVE / RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 24° LED 1550lm/840 1x12W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 24° LED 2400lm/830 1x19W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 24° LED 2500lm/840 1x19W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 24° LED 3550lm/830 1x31W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 24° LED 3650lm/840 1x31W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 40° LED 1500lm/830 1x12W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 40° LED 1550lm/840 1x12W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 40° LED 2400lm/830 1x19W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 40° LED 2500lm/840 1x19W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 40° LED 3550lm/830 1x31W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
ZIPAR ADJUSTABLE 40° LED 3650lm/840 1x31W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.