



### PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



### Accessories



# AILIN

## DOWNLOADS

[Datasheet](#)

[Installation manual](#)

### Description

<b>MOUNTING</b>	Ceiling recessed
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Opal diffuser (OPD)
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear FIX / DALI (ECG / EDA) Emergency unit variant (3H, ECG)
<b>MATERIALS</b>	Diffuser: PMMA Holder: sheet steel Housing: extruded aluminium
<b>SURFACE FINISH</b>	Housing: elox
<b>AMBIENT OPERATING TEMPERATURE</b>	From -20 °C to +35 °C (from +5°C with EM unit)

### AREAS OF APPLICATION

- ARCHITECTURE AND MEDIA
- EDUCATION
- HOSPITALITY
- HOUSE AND FLAT
- RETAIL AND PRESENTATION



## List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
AILIN M OPAL LED 3700lm/830 1x38W, FIX, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN M OPAL LED 4000lm/840 1x38W, FIX, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN L OPAL LED 4650lm/830 1x47W, FIX, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN L OPAL LED 4950lm/840 1x47W, FIX, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN M OPAL LED 3700lm/830 1x38W, DALI, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN M OPAL LED 4000lm/840 1x38W, DALI, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN L OPAL LED 4950lm/840 1x47W, DALI, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN L OPAL LED 3800lm/840 1x47W, DALI, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN M OPAL LED 3700lm/830 1x38W, FIX + EM 3H, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN M OPAL LED 4000lm/840 1x38W, FIX + EM 3H, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN L OPAL LED 4650lm/830 1x47W, FIX + EM 3H, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN L OPAL LED 4950lm/840 1x47W, FIX + EM 3H, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.