



PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



DOWNLOADS

[Datasheet](#)
[Installation manual](#)

AILIN XTP

Description

MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Opal diffuser (OPD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX / DALI (ECG / EDA) Emergency unit variant (3H)
MATERIALS	Diffuser: PMMA Holder: sheet steel Housing: extruded aluminium
SURFACE FINISH	Housing: elox
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C (from +5°C with EM unit)

AREAS OF APPLICATION

- ARCHITECTURE AND MEDIA
- EDUCATION
- HOSPITALITY
- HOUSE AND FLAT
- RETAIL AND PRESENTATION



Accessories

List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
AILIN XTP M OPAL LED 2950lm/830 1x37W, FIX, Elox		RFA / 3DS / IES / LDT / CURVE /
AILIN XTP M OPAL LED 3050lm/840 1x37W, FIX, Elox		RFA / 3DS / IES / LDT / CURVE /
AILIN XTP L OPAL LED 3650lm/830 1x47W, FIX, Elox		RFA / 3DS / IES / LDT / CURVE /
AILIN XTP L OPAL LED 3800lm/840 1x47W, FIX, Elox		RFA / 3DS / IES / LDT / CURVE /
AILIN XTP M OPAL LED 2950lm/830 1x37W, DALI, Elox		RFA / 3DS / IES / LDT / CURVE /
AILIN XTP M OPAL LED 3050lm/840 1x37W, DALI, Elox		RFA / 3DS / IES / LDT / CURVE /
AILIN XTP L OPAL LED 3650lm/830 1x47W, DALI, Elox		RFA / 3DS / IES / LDT / CURVE /
AILIN XTP L OPAL LED 3800lm/840 1x47W, DALI, Elox		RFA / 3DS / IES / LDT / CURVE /
AILIN XTP M OPAL LED 2950lm/830 1x37W, FIX + EM 3H, Elox		RFA / 3DS / IES / LDT / CURVE /
AILIN XTP M OPAL LED 3050lm/840 1x37W, FIX + EM 3H, Elox		RFA / 3DS / IES / LDT / CURVE /
AILIN XTP L OPAL LED 3650lm/830 1x47W, FIX + EM 3H, Elox		RFA / 3DS / IES / LDT / CURVE /
AILIN XTP L OPAL LED 3800lm/840 1x47W, FIX + EM 3H, Elox		RFA / 3DS / IES / LDT /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.