



### PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



## DOWNLOADS

[Datasheet](#)

[Installation manual](#)

# AILIN TRIMLESS

### Description

<b>MOUNTING</b>	Ceiling recessed
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Opal diffuser (OPD)
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear FIX / DALI (ECG / EDA) Emergency unit variant (3H)
<b>MATERIALS</b>	Diffuser: opal PMMA Holder: sheet steel Housing: extruded aluminium
<b>SURFACE FINISH</b>	Housing: elox
<b>SERVICE LIFETIME (Ta=25°C)</b>	50,000 hours / L80 / B10
<b>AMBIENT OPERATING TEMPERATURE</b>	From -20 °C to +35 °C (from 0 °C with EM unit)

- AREAS OF APPLICATION**
- ARCHITECTURE AND MEDIA
  - EDUCATION
  - RETAIL AND PRESENTATION



## Accessories

---

## List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
AILIN TRIMLESS M OPAL LED 2950lm/830 1x37W, LED DRIVER, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN TRIMLESS M OPAL LED 3050lm/840 1x37W, LED DRIVER, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN TRIMLESS L OPAL LED 3650lm/830 1x47W, LED DRIVER, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
AILIN TRIMLESS L OPAL LED 3800lm/840 1x47W, LED DRIVER, Elox		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.