



### PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



### DOWNLOADS

[Datasheet](#)

[Installation manual](#)

# REBELL II

### Description


<b>MOUNTING</b>	Suspended (SSD)
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Reflector (REF)
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear FIX / DALI (ECG / EDA)
<b>MATERIALS</b>	Housing: injected PC Reflector: anodised aluminium Ring: injected PC Rope suspension
<b>SURFACE FINISH</b>	Standard surface finish in versions EXCLUSIVE white or black
<b>ACCESSORIES</b>	Chain suspension CHS 66
<b>SERVICE LIFETIME (Ta=25°C)</b>	50,000 hours / L80 / B10
<b>AMBIENT OPERATING TEMPERATURE</b>	From -20 °C to +35 °C

**AREAS OF APPLICATION** ARCHITECTURE AND MEDIA

RETAIL AND PRESENTATION



## Accessories



## List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
REBELL II REF LED 5300lm/830 1x55W, FIX, EV1	Updated	<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
REBELL II REF LED 5300lm/830 1x55W, FIX, EV2	Updated	<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
REBELL II REF LED 5300lm/830 1x55W, DALI, EV1	Updated	<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
REBELL II REF LED 5300lm/830 1x55W, DALI, EV2	Updated	<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
REBELL II REF LED 5450lm/840 1x55W, FIX, EV1	Updated	<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
REBELL II REF LED 5450lm/840 1x55W, FIX, EV2	Updated	<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
REBELL II REF LED 5450lm/840 1x55W, DALI, EV1	Updated	<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
REBELL II REF LED 5450lm/840 1x55W, DALI, EV2	Updated	<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.