



PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



Accessories



DOWNLOADS

[Datasheet](#)

[Installation manual](#)

PLAST B

Description

MOUNTING	Ceiling surfaced (SFD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Opal diffuser (OPD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG) Microwave sensor
MATERIALS	Housing: polycarbonate Diffuser: polycarbonate
SERVICE LIFETIME (Ta=25°C)	40,000 hours / L70 / B50
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C

AREAS OF APPLICATION

- HOSPITALITY
- HOUSE AND FLAT
- HEALTH AND CARE



List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
PLAST B OPAL LED 2200lm/830 1x25W, FIX, -		RFA / 3DS / IES / LDT / CURVE /
PLAST B OPAL LED 2300lm/840 1x25W, FIX, -		RFA / 3DS / IES / LDT / CURVE /
PLAST B OPAL LED 2200lm/830 1x25W, FIX + SENSOR, -		RFA / 3DS / IES / LDT / CURVE /
PLAST B OPAL LED 2300lm/840 1x25W, FIX + SENSOR, -		RFA / 3DS / IES / LDT / CURVE /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.