




PRODUCT DETAILS



Dimensions



Accessories



ZIPAR II TRACK

ZIPAR II TRACK 24° LED 1550lm/840
1x12W, FIX, RAL 9003

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description


MOUNTING	Suspended or ceiling surfaced lighting track system - suitable for ONETRACK (TRS)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Facet reflector (FRE)
BEAM ANGLE	24°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Cover: transparent hardened glass Housing: die-cast aluminium Reflector: facet anodised aluminium
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Exchangeable reflectors Various types of connections and suspension equipment (ONETRACK)
VOLTAGE	220-240 V, 50-60 Hz
NET LUMEN OUTPUT (Ta=25°C)	1550 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	12 W
SYSTEM EFFICACY	129 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>80 Ra
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	172 x 92 x 155 mm
TILTING	Up to 350°
ROTATING	Up to 350°
WEIGHT	1 kg

AREAS OF APPLICATION ARCHITECTURE AND MEDIA
 RETAIL AND PRESENTATION





LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.