




PRODUCT DETAILS



Dimensions



Accessories



ELYS TRACK TW

ELYS TRACK TW 24° LED 1800lm/9TW
1x27W, DALI, RAL 9003

DOWNLOADS


[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Suspended or ceiling surfaced lighting track system - suitable for ONETRACK (TRS)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Facet reflector (FRE)
BEAM ANGLE	24°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear DALI (EDA)
MATERIALS	Cover: transparent hardened glass Housing: die-cast aluminium Reflector: facet anodised aluminium
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Exchangeable reflectors Various types of connections and suspension equipment (ONETRACK)
VOLTAGE	220-240 V, 50-60 Hz
NET LUMEN OUTPUT (Ta=25°C)	1800 lm - 1900 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	27 W
SYSTEM EFFICACY	67-70 lm/W
CORRELATED COLOUR TEMPERATURE	2700-5700 K
COLOUR RENDERING INDEX	>90 Ra
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L70 / B50
AMBIENT OPERATING TEMPERATURE	From -25 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	172 x 92 x 155 mm
TILTING	Up to 350°
ROTATING	Up to 350°
WEIGHT	1,1 kg

AREAS OF APPLICATION ARCHITECTURE AND MEDIA
 RETAIL AND PRESENTATION

LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.