



PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



Accessories



DOWNLOADS

[Datasheet](#)

[Installation manual](#)

ELYS TRACK TW

Description

MOUNTING

Suspended or ceiling surfaced lighting track system - suitable for ONETRACK (TRS)

LIGHT SOURCE

LED

OPTICAL SYSTEM

Facet reflector (FRE)

LIGHT DISTRIBUTION

Direct

WIRING

Electronic control gear DALI (EDA)

MATERIALS

Cover: transparent hardened glass

Housing: die-cast aluminium

Reflector: facet anodised aluminium

Housing: white RAL 9003 (W03)

SURFACE FINISH

ACCESSORIES

Exchangeable reflectors

Various types of connections and suspension equipment (ONETRACK)

SERVICE LIFETIME (Ta=25°C)

50,000 hours / L70 / B50

AMBIENT OPERATING

TEMPERATURE

From -25 °C to +35 °C

AREAS OF APPLICATION

ARCHITECTURE AND MEDIA

RETAIL AND PRESENTATION



List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
ELYS TRACK TW 24° LED 1800lm/9TW 1x27W, DALI, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
ELYS TRACK TW 30° LED 1800lm/9TW 1x27W, DALI, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
ELYS TRACK TW 50° LED 1800lm/9TW 1x27W, DALI, RAL 9003		RFA / 3DS / IES / LDT / CURVE /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.