




PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



Accessories



DOWNLOADS

[Datasheet](#)

[Installation manual](#)

ALASTAR C TRIMLESS

Description

MOUNTING	Ceiling recessed (TMS)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Opal diffuser (OPD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX / DALI (ECG / EDA)
MATERIALS	Diffuser: PMMA Holder: sheet steel Housing: extruded aluminium
SURFACE FINISH	Housing: grey RAL 9006 (G06)
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C

AREAS OF APPLICATION

- ARCHITECTURE AND MEDIA
- HOSPITALITY
- HOUSE AND FLAT
- HEALTH AND CARE
- RETAIL AND PRESENTATION



List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
ALASTAR C TRIMLESS S OPAL LED 2250lm/830 1x18W, FIX, RAL 9006		RFA / 3DS / IES / LDT / CURVE /
ALASTAR C TRIMLESS S OPAL LED 2400lm/840 1x18W, FIX, RAL 9006		RFA / 3DS / IES / LDT / CURVE /
ALASTAR C TRIMLESS M OPAL LED 4500lm/830 1x36W, FIX, RAL 9006		RFA / 3DS / IES / LDT / CURVE /
ALASTAR C TRIMLESS M OPAL LED 4800lm/840 1x36W, FIX, RAL 9006		RFA / 3DS / IES / LDT / CURVE /
ALASTAR C TRIMLESS L OPAL LED 8500lm/830 1x73W, FIX, RAL 9006		RFA / 3DS / IES / LDT / CURVE /
ALASTAR C TRIMLESS L OPAL LED 9000lm/840 1x73W, FIX, RAL 9006		RFA / 3DS / IES / LDT / CURVE /
ALASTAR C TRIMLESS S OPAL LED 2250lm/830 1x18W, DALI, RAL 9006		RFA / 3DS / IES / LDT / CURVE /
ALASTAR C TRIMLESS S OPAL LED 2400lm/840 1x18W, DALI, RAL 9006		RFA / 3DS / IES / LDT / CURVE /
ALASTAR C TRIMLESS M OPAL LED 4500lm/830 1x36W, DALI, RAL 9006		RFA / 3DS / IES / LDT / CURVE /
ALASTAR C TRIMLESS M OPAL LED 4800lm/840 1x36W, DALI, RAL 9006		RFA / 3DS / IES / LDT / CURVE /
ALASTAR C TRIMLESS L OPAL LED 8500lm/830 1x73W, DALI, RAL 9006		RFA / 3DS / IES / LDT / CURVE /
ALASTAR C TRIMLESS L OPAL LED 9000lm/840 1x73W, DALI, RAL 9006		RFA / 3DS / IES / LDT /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.