



PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



Accessories



DOWNLOADS

[Datasheet](#)

[Installation manual](#)

AIR IB

Description

MOUNTING	Suspended or ceiling surfaced lighting track system - suitable for ONETRACK (TRS)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Facet reflector (FRE)
BEAM ANGLE	24° 40°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Housing: die-cast aluminium + sheet steel Reflector: facet anodised aluminium
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Various types of connections and suspension equipment (ONETRACK)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	0,95
LUMINOUS FLUX TOLERANCE	+/- 10 %
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C

AREAS OF APPLICATION ARCHITECTURE AND MEDIA
 RETAIL AND PRESENTATION



List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
AIR IB 24° LED 2250lm/830 1x21W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
AIR IB 40° LED 2250lm/830 1x21W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
AIR IB 24° LED 2350lm/840 1x21W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
AIR IB 40° LED 2350lm/840 1x21W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
AIR IB 24° LED 3800lm/830 1x36W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
AIR IB 40° LED 3800lm/830 1x36W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
AIR IB 24° LED 3900lm/840 1x36W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
AIR IB 40° LED 3900lm/840 1x36W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.