



PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



DOWNLOADS

[Datasheet](#)

[Installation manual](#)

LAMBDA LED D-I S+

Description

MOUNTING	Suspended (SSD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Microprismatic diffuser (MCD)
BEAM ANGLE	70°, 87°
LIGHT DISTRIBUTION	Direct-indirect
WIRING	External lead-in flexible cable Electronic control gear DALI + SENSOR (D2S)
MATERIALS	Diffuser: PMMA Housing: sheet steel
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Rope suspension RS-S 58 IR Programming Tool
SERVICE LIFETIME (Ta=25°C)	100,000 hours / L90 / B10
AMBIENT OPERATING TEMPERATURE	From 0 °C to +35 °C

AREAS OF APPLICATION


EDUCATION

HEALTH AND CARE

OFFICE



Accessories



List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
LAMBDA LED D-I S+ M LED 5500lm/840 1x37W, DALI, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
LAMBDA LED D-I S+ L LED 6200lm/840 1x42W, DALI, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.