



### PRODUCT DETAILS



VIBA series STANDARD PRODUCTS PROJECT PRODUCTS UPDATED  
PRODUCTS PHASE-OUT PRODUCTS



### Accessories



### DOWNLOADS

[Datasheet](#)

[Installation manual](#)

# LAMBDA LED D-I S+

### Description

<b>MOUNTING</b>	Suspended (SSD)
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Microprismatic diffuser (MCD)
<b>LIGHT DISTRIBUTION</b>	Direct-indirect
<b>WIRING</b>	External lead-in flexible cable Electronic control gear DALI + SENSOR (D2S)
<b>MATERIALS</b>	Diffuser: PMMA Housing: sheet steel
<b>SURFACE FINISH</b>	Housing: white RAL 9003 (W03)
<b>ACCESSORIES</b>	Rope suspension RS-S 58 IR Programming Tool
<b>AMBIENT OPERATING TEMPERATURE</b>	From -20 °C to +35 °C

### AREAS OF APPLICATION

EDUCATION

HEALTH AND CARE

OFFICE





## List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
LAMBDA LED D-I S+ M LED 5500lm/840 1x37W, DALI + SENSOR (D2S), RAL 9003		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
LAMBDA LED D-I S+ L LED 6200lm/840 1x42W, DALI + SENSOR (D2S), RAL 9003		<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.