



PRODUCT DETAILS



Dimensions



Accessories



AILIN LINE TRIMLESS

AILIN LINE TRIMLESS M F OPAL LED
3050lm/840 1x37W, FIX + EM 3H, Elox

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Ceiling recessed - determined for continuous installation
LIGHT SOURCE	LED
OPTICAL SYSTEM	Opal diffuser (OPD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG) Through wiring (F, T version) Emergency unit variant (3H)
MATERIALS	Diffuser: PMMA Holder: sheet steel Housing: extruded aluminium Housing: elox
SURFACE FINISH	Housing: elox
ACCESSORIES	Connecting piece (L/T/X)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	3050 lm (140 lm-emergency unit)
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	37 W
SYSTEM EFFICACY	82 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	I
THERMAL MANAGEMENT	Passive
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C (from +5°C with EM unit)
IP PROTECTION DEGREE	IP40
DIMENSIONS	First piece - 1162 mm, through piece - 1160 mm, last piece - 1162 mm, width - 82 mm, height - 77 mm
OPENING	First piece - 1165 mm, through piece - 1163 mm, last piece - 1165 mm, width - 85 mm

--- 902030



--- 902030



--- 902031



--- 902031



--- 902032



--- 902032




--- 902033



--- 902 033



LIDC



WEIGHT

First piece - 3,3 kg, through piece - 2,9 kg,
last piece - 2,9 kg

AREAS OF APPLICATION

ARCHITECTURE AND MEDIA

EDUCATION

HOSPITALITY

HOUSE AND FLAT

RETAIL AND PRESENTATION



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.