



PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



DOWNLOADS

[Datasheet](#)

[Installation manual](#)

MILINE UNO RECESSED

Description

MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Lenses + white louvre (LWL)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX / DALI (ECG / EDA) Emergency unit variant (3H, ECG)
MATERIALS	Housing: sheet steel Louvre: polycarbonate
SURFACE FINISH	Housing: white RAL 9003 (W03)
SERVICE LIFETIME (Ta=25°C)	100,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -25 °C to +35 °C (from +5°C with EM unit)

AREAS OF APPLICATION EDUCATION

OFFICE



Accessories

List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
MILINE UNO RECESSED M LED 3300lm/830 1x23W, FIX, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED M LED 3300lm/830 1x23W, DALI, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED M LED 3300lm/830 1x23W, FIX + EM 3H, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED M LED 3450lm/840 1x23W, FIX, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED M LED 3450lm/840 1x23W, DALI, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED M LED 3450lm/840 1x23W, FIX + EM 3H, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED M LED 4350lm/830 1x31W, FIX, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED M LED 4350lm/830 1x31W, DALI, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED M LED 4350lm/830 1x31W, FIX + EM 3H, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED M LED 4500lm/840 1x31W, FIX, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED M LED 4500lm/840 1x31W, DALI, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED M LED 4500lm/840 1x31W, FIX + EM 3H, RAL 9003	New	RFA / 3DS / IES / LDT /

MILINE UNO RECESSED L LED 4100lm/830 1x27W, FIX, RAL 9003	New	CURVE / RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED L LED 4100lm/830 1x27W, DALI, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED L LED 4100lm/830 1x27W, FIX + EM 3H, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED L LED 4300lm/840 1x27W, FIX, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED L LED 4300lm/840 1x27W, DALI, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED L LED 4300lm/840 1x27W, FIX + EM 3H, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED L LED 5500lm/830 1x38W, FIX, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED L LED 5500lm/830 1x38W, DALI, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED L LED 5500lm/830 1x38W, FIX + EM 3H, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED L LED 5800lm/840 1x38W, FIX, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED L LED 5800lm/840 1x38W, DALI, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /
MILINE UNO RECESSED L LED 5800lm/840 1x38W, FIX + EM 3H, RAL 9003	New	RFA / 3DS / IES / LDT / CURVE /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.