



PRODUCT DETAILS



Dimensions



Accessories



RELAX AA / A2 / A1 / A8 LED S+

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)


**RELAX AA / A2 / A1 / A8 LED S+ AA 2S S+ LED 3750lm/840
1x26W, DALI + SENSOR (D2S), RAL 9003**

Description

MOUNTING	Ceiling recessed PVx - T-ceiling
LIGHT SOURCE	LED
OPTICAL SYSTEM	Matt parabolic louvre PAR MAT-V2 (ML2)
BEAM ANGLE	70°, 90°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear DALI + SENSOR (D2S)
MATERIALS	Diffuser: PMMA Housing: sheet steel Parabolic louvre: matt anodised aluminium Housing: white RAL 9003 (W03)
SURFACE FINISH	
ACCESSORIES	Frame for plasterboard installation IR Programming Tool
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	0,92
NET LUMEN OUTPUT (Ta=25°C)	3750 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	26 W
SYSTEM EFFICACY	144 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>80 Ra
COLOUR TOLERANCE	3 SDCM
PROTECTION CLASS	I
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L90 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
WEIGHT	4,3 kg



LIDC



AREAS OF APPLICATION OFFICE



5 YEARS WARRANTY



EEC
A++/A+



MAINTENANCE
FREE



UV/IR



ECO
FRIENDLY



ENERGY
SAVING

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.