




PRODUCT DETAILS



Dimensions



Accessories



ZIPAR II MOVABLE

ZIPAR II MOVABLE 24° LED 2500lm/840 1x19W, DALI, RAL 9003

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[EEC](#)

Description

MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Facet reflector (FRE)
BEAM ANGLE	24°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear DALI (EDA)
MATERIALS	Cover: transparent hardened glass Housing: die-cast aluminium Reflector: facet anodised aluminium Housing: white RAL 9003 (W03)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	2500 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	19 W
SYSTEM EFFICACY	132 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	80 Ra
THERMAL MANAGEMENT	Passive
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS	Diameter - 80 mm, height - 177 mm
TILTING	Up to 270°
ROTATING	Up to 350°
WEIGHT	1,3 kg

AREAS OF APPLICATION ARCHITECTURE AND MEDIA
 HOSPITALITY
 RETAIL AND PRESENTATION

LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.