




PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



Accessories



DOWNLOADS

[Datasheet](#)

[Installation manual](#)

RELAX H LED S+

Description

| | |
|--------------------------------------|---|
| MOUNTING | Ceiling recessed |
| LIGHT SOURCE | LED |
| OPTICAL SYSTEM | Matt parabolic louvre PAR MAT-V2 (ML2) |
| LIGHT DISTRIBUTION | Direct |
| WIRING | Electronic control gear DALI + SENSOR (D2S) |
| MATERIALS | Diffuser: PMMA Housing: sheet steel Parabolic louvre: matt anodised aluminium |
| SURFACE FINISH | Housing: white RAL 9003 (W03) |
| ACCESSORIES | IR Programming Tool |
| SERVICE LIFETIME (Ta=25°C) | 100,000 hours / L90 / B10 |
| AMBIENT OPERATING TEMPERATURE | From -20 °C to +35 °C |

AREAS OF APPLICATION EDUCATION OFFICE



List of products

| PRODUCT NAME | STATUS | QUICK DOWNLOADS |
|--|---------|--|
| RELAX H LED S+ M LED 4500lm/840 1x32W, DALI + SENSOR (D2S), RAL 9003 | Updated | RFA / 3DS / IES / LDT / CURVE / |
| RELAX H LED S+ L LED 7050lm/840 1x50W, DALI + SENSOR (D2S), RAL 9003 | Updated | RFA / 3DS / IES / LDT / CURVE / |

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.